Data Sheet



SENCITY® Spot-S WiFi Antenna 1356.26.0017

SPA-5600/40/14/0/V_2

Description

Directional, planar, linear vertical polarized WiFi antenna with 14 dBi gain

WLAN IEEE 802.11 a/h/p - WiFi bands 5.15 to 5.975 GHz

Approved acc. to EN 50155 (2007) and EN 45545-2 (2012) for railway rolling stock

For outdoor and indoor applications Ingress protection IP 66 and IP 67

Wall mounting material included



Product Configuration

Technical Data

Electrical Data

	Band 1
Frequency (MHz)	5150 - 5975
VSWR	1.5
Impedance (Ohm)	50
Gain (dBi)	14
3dB beamwidth (h) (°)	40
3dB beamwidth (v) (°)	35
Front to back ratio (dB)	20
Vertical electrical tilt (°)	0

Ports

	Port 1
Connector	TNC, jack (female)
Polarization	vertical

General Data

DC Grounding Yes
Composite Power max (W) 10

- Meets EN 50155 railway standard fire retardant acc. to DIN 5510-2, EN 45545-2, BS 6853, and outdoor use acc. to NF F16-101/102
- Meets environmental standards according to EN 60068

Mechanical Data

Dimensions (mm) 101 x 81 x 36 (Heigth x Width x Depth)

Weight (kg) 0.1

Windload frontal: 15 N at 160 km/h , Wind speed survival: 220 km/h

Included mounting material Wall mounting material

Environmental Data

Environmental conditions outdoor Operation temperature (°C) -40 to 85 Storage temperature (°C) -40 to 85 Transport temperature (°C) -40 to 85 EN 45545-2 Flammability rating RoHS 2011/65/EC compliant Lead-free soldered yes REACH 2006/1907/EC compliant

IP RATING: IP 66 / IP 67 (IEC 60529)

SOLAR RADIATION: EN 50125-3:2004 §4.9, 1120 W/m² for 20h

Document: DOC-0000333818 AB / PDO AG / date of publication: 17.07.2016 17:32:09 / uncontrolled copy

Data Sheet



SENCITY® Spot-S WiFi Antenna 1356.26.0017

RAIN: EN 50125-3:2004 §4.6, delivery rate: 6 mm/min CORROSION: MIL-F-14072 E Type 1 "exposed"

Material Data

Radome colour RAL 7044 (grey)
Radome material PC (Polycarbonate)

Related Products

9091.99.0238 Outdoor Spot-S Antenna Down-Sidetilt Bracket 9091.99.0237 L-Bracket for SPOT-S antennas

Related Documents

 Mounting instruction
 DOC-0000287053

 Painting instruction
 DOC-0000256180

 Security instruction
 DOC-0000278984

 Outline drawing
 DOU-00139616

 3D-model
 DOC-0000411476

Additional Information

Following Declaration of Conformity for SENCITY® Spot-S antennas are available on request: * Industrial standards EN 60068 / EN 60529 / IEC 61373 s ref. DOC-0000318049 * Railway rolling stock, environmental standards EN 50155 and fire behaviour EN 45545-2 ref. DOC-0000380375

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

1356.26.0017