

LOADED CONNECTOR ASSEMBLY
(FOR EXAMPLE)

EXAMPLE)

Technical drawing of a cable tray assembly showing top, side, and detail views with dimensions and callouts.

Top View:

- Overall width: 20.0
- Segment width (10x): 2.00 ± 0.05 (10x)
- Segment width (10x): 2.00 ± 0.05 (10x)

Side View:

- Overall height: 12.0
- Segment height (6x): 2.00 ± 0.05 (6x)
- Overall length: 50.0 MAX.


Detail View (Note 3):

- Overall width: 15.40 ± 0.50
- Segment width (10x): 11.70 ± 0.10
- Segment width (10x): 3.00 ± 0.08
- Segment height (6x): 13.45 ± 0.1
- Segment height (6x): 4.0 ± 0.15

Callouts:

- note 5
- note 3
- note 6

LAY-OUT P.C.B.-HOLE



HM2P07PDN2C4

LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

PLATING CODE (DIGIT 13 AND 14)
(REF DWG No. BS.C ,201844,003)

NOTES:

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASSFILLED
POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN
MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER
DEPENDING ON PRODUCTION LOCATION.
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS.A ,201572.001

1DEC ± 0.2 2DEC ± 0.1 ANGLES $\pm 1^\circ$	APPR.	DATE	SIGN.	MPACS 5+2R STR HDR SG PF CONN TYPE A
	DRAFT	2001-01-16	M.Fret	CAT. No. HM2P07PDN2C4----  www.fciconnect.com
	CHECKED			
WE RESERVE THE RIGHT TO CHANGE DIMENSIONS OR REQUIREMENTS WITHOUT PRIOR NOTICE.	PROD. MGR.			 www.fciconnect.com
	PR. ENG. MGR.			
ALL DIMENSIONS IN MM	PR. MGT. MGR.			 www.fciconnect.com
 	REFERENCES			BS, C , 202788 , 074 D DRAWING No. CUSTOMER DRAWING REVISION

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P07PDN2C4N9LF](#) [HM2P07PDN2C4N9](#)