

f	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	
e	4	4	4	4	4	4	4	4	4	4				4	4	4	4	4	4	4	4	5	5	6
d	4	4	4	4	4	4	4	4	4	4				4	4	4	4	4	4	5	4	5	5	6
c	4	4	4	4	4	4	4	4	4	4				4	4	4	4	4	4	5	6	5	5	6
b	4	4	4	4	4	4	4	4	4	4				4	4	4	4	4	4	5	6	5	5	6
a	4	4	4	4	4	4	4	4	4	4				4	4	4	4	4	4	5	6	5	5	6
z	0	0	0	0	0	0	0	0	0	0				0	0	0	0	0	0	0	0	0	0	0
P																								
O	0				5				1				5				2				2			
S	1				5				0				5				0				5			

Diagram illustrating the dimensions of three different connector types (4, 5, and 6) relative to a vertical line representing the seating plane for the connector.

The dimensions are as follows:

- Connector 4: Length = 8.20, Width = 3.70
- Connector 5: Length = 9.70, Width = 3.70
- Connector 6: Length = 11.20, Width = 3.70

Figure 1: Plan view of the reinforced concrete slab. The slab is 20.00m long and 8.00m wide. It features a central 8.00m wide opening. Reinforcement is shown as a grid of circles and squares. Dimensions for reinforcement spacing are given as 2.00m, 4.00m, and 2.00m. A detail callout shows a circle with diameter 2.00m and a vertical offset of +0.05m from the bottom.

LEAD FREE INDICATOR : LF = LEAD FREE
(DIGIT 15 & 16)

PLATING CODE (DIGIT 13 AND 14)
(REF DRW NO. BS,C , 201844 , 003)

1. THIS PRODUCT IS CSA APPROVED.
2. THIS PRODUCT IS UL RECOGNIZED.
3. MEASURED AT THE BOTTOM.
4. MATERIAL CONTACT: PHOSPHORBRONZE
HOUSING: CREAM WHITE GLASS FILLED POLYESTER UL-94V0
5. CONNECTOR PRINTED WITH P/N AND DATE CODE.
6. FOR ACTUAL CONTACT LOADINGS, SEE LOADING PATTERN MATING SIDE.
7. SHAPE OF CONNECTOR HOUSING CAN ALTER DEPENDING ON
PRODUCTION LOCATION
8. THE PRODUCT (LF) MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-22-008
9. FOR RECOMMENDED PTH DIMENSIONS REFER DRAWING : BS, A , 201572 , 001

CATALOG NO: HM2P07PDH3R0----

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P07PDH3R0N9](#) [HM2P07PDH3R0N9LF](#)