

f	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K		
e	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
d	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
c	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
b	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
a	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5		
z	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K	K		
P	0					0					1					1					2					2
S	1					5					0					5					0					5

The technical drawings illustrate the bridge deck geometry. The cross-section (left) shows a total width of 15.40 ± 0.50 m, with a central width of 11.70 ± 0.10 m (NOTE 3). The deck height is $13.45^{+0.15}_{-0.10}$ m, and the bottom width is $3.00^{+0}_{-0.10}$ m. The plan view (right) shows a total length of 48.00 m and a width of 50.0 MAX. The deck is divided into sections with dimensions 12.00 m and $2.00 \pm 0.05 (6x)$ m. The bottom width is $2.00 \pm 0.05 (24x)$ m. A dashed rectangle indicates the location of the bridge piers (NOTE 5). The drawings are labeled with dimensions and notes (NOTE 3, NOTE 5, NOTE 6).

SEATING PLANE FOR CONNECTOR

5

9.70 3.70

F

9.70 16.00

K

11.20 16.00

A diagram of a rectangular field with a width of 48.00 and a height of 12.00. The field is filled with a grid of points, with 12 rows and 40 columns of points. The points are represented by small circles. The dimensions are indicated by arrows and labels: 48.00 for the width and 12.00 for the height.

CATALOG NO: HM2P08PNK344----

[illegible]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[HM2P08PNK344GFLF](#)