

EconoPACK™3 module with Trench/Fieldstop IGBT4 and Emitter Controlled diode and NTC

Features

- Electrical features
 - $V_{CES} = 1700\text{ V}$
 - $I_{C\text{ nom}} = 150\text{ A} / I_{CRM} = 300\text{ A}$
 - Low V_{CESat}
 - $T_{vj\text{ op}} = 150\text{ °C}$
 - Trench IGBT 4
 - V_{CESat} with positive temperature coefficient
- Mechanical features
 - Integrated NTC temperature sensor
 - Standard housing
 - Solder contact technology
 - Isolated base plate



Typical appearance

Potential applications

- High power converters
- Medium voltage converters

Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

Description




Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT, Inverter	3
3	Diode, Inverter	5
4	Diode, Rectifier	6
5	NTC-Thermistor	7
6	Characteristics diagrams	8
7	Circuit diagram	12
8	Package outlines	12
	Revision history	13
	Disclaimer	14

1 Package

1 Package

Table 1 Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	V_{ISOL}	RMS, $f = 50 \text{ Hz}$, $t = 1 \text{ min}$	3.4	kV
Material of module baseplate			Cu	
Internal Isolation		basic insulation (class 1, IEC 61140)	Al_2O_3	
Creepage distance	d_{Creep}	terminal to heatsink	10.0	mm
Clearance	d_{Clear}	terminal to heatsink	7.5	mm
Comparative tracking index	CTI		> 225	
RTI Elec.	RTI	housing	140	°C

Table 2 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	L_{SCE}			33		nH
Module lead resistance, terminals - chip	$R_{AA'+CC'}$	$T_C = 25^\circ\text{C}$, per switch		3		mΩ
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_C = 25^\circ\text{C}$, per switch		2		mΩ
Storage temperature	T_{stg}		-40		125	°C
Mounting torque for modul mounting	M	- Mounting according to valid application note	3		6	Nm
Weight	G			300		g

2 IGBT, Inverter

Table 3 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Collector-emitter voltage	V_{CES}		$T_{vj} = 25^\circ\text{C}$	1700	V
Implemented collector current	I_{CN}			150	A
Continuous DC collector current	I_{CDC}	$T_{vj \max} = 175^\circ\text{C}$	$T_C = 90^\circ\text{C}$	150	A
Repetitive peak collector current	I_{CRM}	$t_p = 1 \text{ ms}$		300	A
Gate-emitter peak voltage	V_{GES}			±20	V

Table 4 **Characteristic values**

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CE\ sat}$	$I_C = 150\ A, V_{GE} = 15\ V$	$T_{vj} = 25\ ^\circ C$		1.70	2.20	V
			$T_{vj} = 125\ ^\circ C$		2.05		
			$T_{vj} = 150\ ^\circ C$		2.10		
Gate threshold voltage	V_{GEth}	$I_C = 6\ mA, V_{CE} = V_{GE}, T_{vj} = 25\ ^\circ C$		5.35	5.80	6.25	V
Gate charge	Q_G	$V_{GE} = \pm 15\ V$			1.53		μC
Internal gate resistor	R_{Gint}	$T_{vj} = 25\ ^\circ C$			4.6		Ω
Input capacitance	C_{ies}	$f = 1000\ kHz, T_{vj} = 25\ ^\circ C, V_{CE} = 25\ V, V_{GE} = 0\ V$			12.3		nF
Reverse transfer capacitance	C_{res}	$f = 1000\ kHz, T_{vj} = 25\ ^\circ C, V_{CE} = 25\ V, V_{GE} = 0\ V$			0.4		nF
Collector-emitter cut-off current	I_{CES}	$V_{CE} = 1700\ V, V_{GE} = 0\ V$	$T_{vj} = 25\ ^\circ C$			1	mA
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\ V, V_{GE} = 20\ V, T_{vj} = 25\ ^\circ C$				100	nA
Turn-on delay time (inductive load)	t_{don}	$I_C = 150\ A, V_{CE} = 900\ V, V_{GE} = \pm 15\ V, R_{Gon} = 0.91\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.205		μs
			$T_{vj} = 125\ ^\circ C$		0.228		
			$T_{vj} = 150\ ^\circ C$		0.234		
Rise time (inductive load)	t_r	$I_C = 150\ A, V_{CE} = 900\ V, V_{GE} = \pm 15\ V, R_{Gon} = 0.91\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.064		μs
			$T_{vj} = 125\ ^\circ C$		0.074		
			$T_{vj} = 150\ ^\circ C$		0.076		
Turn-off delay time (inductive load)	t_{doff}	$I_C = 150\ A, V_{CE} = 900\ V, V_{GE} = \pm 15\ V, R_{Goff} = 0.91\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.525		μs
			$T_{vj} = 125\ ^\circ C$		0.680		
			$T_{vj} = 150\ ^\circ C$		0.713		
Fall time (inductive load)	t_f	$I_C = 150\ A, V_{CE} = 900\ V, V_{GE} = \pm 15\ V, R_{Goff} = 0.91\ \Omega$	$T_{vj} = 25\ ^\circ C$		0.594		μs
			$T_{vj} = 125\ ^\circ C$		0.833		
			$T_{vj} = 150\ ^\circ C$		0.892		
Turn-on energy loss per pulse	E_{on}	$I_C = 150\ A, V_{CE} = 900\ V, L_\sigma = 35\ nH, V_{GE} = \pm 15\ V, R_{Gon} = 0.91\ \Omega, di/dt = 1250\ A/\mu s (T_{vj} = 150\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$		47.6		mJ
			$T_{vj} = 125\ ^\circ C$		63.9		
			$T_{vj} = 150\ ^\circ C$		68.8		
Turn-off energy loss per pulse	E_{off}	$I_C = 150\ A, V_{CE} = 900\ V, L_\sigma = 35\ nH, V_{GE} = \pm 15\ V, R_{Goff} = 0.91\ \Omega, dv/dt = 4150\ V/\mu s (T_{vj} = 150\ ^\circ C)$	$T_{vj} = 25\ ^\circ C$		50.8		mJ
			$T_{vj} = 125\ ^\circ C$		69.3		
			$T_{vj} = 150\ ^\circ C$		74.2		
SC data	I_{SC}	$V_{GE} \leq 15\ V, V_{CC} = 1000\ V, V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$			600		A
Thermal resistance, junction to case	R_{thJC}	per IGBT				0.195	K/W

Table 4 Characteristic values (continued)

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Thermal resistance, case to heatsink	R_{thCH}	per IGBT, $\lambda_{grease} = 1 \text{ W/(m}^2\text{K)}$		0.0700		K/W
Temperature under switching conditions	$T_{vj\text{ op}}$		-40		150	°C

3 Diode, Inverter

Table 5 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Repetitive peak reverse voltage	V_{RRM}	$T_{vj} = 25 \text{ °C}$	1700	V
Continuous DC forward current	I_F		150	A
Repetitive peak forward current	I_{FRM}	$t_P = 1 \text{ ms}$	300	A
I^2t - value	I^2t	$t_P = 10 \text{ ms}, V_R = 0 \text{ V}$	$T_{vj} = 125 \text{ °C}$	A^2s
			$T_{vj} = 150 \text{ °C}$	

Table 6 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$I_F = 150 \text{ A}, V_{GE} = 0 \text{ V}$	$T_{vj} = 25 \text{ °C}$	1.80	2.65	V
			$T_{vj} = 125 \text{ °C}$	1.90		
			$T_{vj} = 150 \text{ °C}$	1.95		
Peak reverse recovery current	I_{RM}	$V_R = 900 \text{ V}, I_F = 150 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 1250 \text{ A/}\mu\text{s} (T_{vj} = 150 \text{ °C})$	$T_{vj} = 25 \text{ °C}$	93.3		A
			$T_{vj} = 125 \text{ °C}$	101		
			$T_{vj} = 150 \text{ °C}$	102		
Recovered charge	Q_r	$V_R = 900 \text{ V}, I_F = 150 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 1250 \text{ A/}\mu\text{s} (T_{vj} = 150 \text{ °C})$	$T_{vj} = 25 \text{ °C}$	33.9		μC
			$T_{vj} = 125 \text{ °C}$	57.9		
			$T_{vj} = 150 \text{ °C}$	64.7		
Reverse recovery energy	E_{rec}	$V_R = 900 \text{ V}, I_F = 150 \text{ A}, V_{GE} = -15 \text{ V}, -di_F/dt = 1250 \text{ A/}\mu\text{s} (T_{vj} = 150 \text{ °C})$	$T_{vj} = 25 \text{ °C}$	17.3		mJ
			$T_{vj} = 125 \text{ °C}$	32.8		
			$T_{vj} = 150 \text{ °C}$	37.1		
Thermal resistance, junction to case	R_{thJC}	per diode			0.365	K/W

Table 6 Characteristic values (continued)

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Thermal resistance, case to heatsink	R_{thCH}	per diode, $\lambda_{grease} = 1 \text{ W/(m}^2\text{K)}$		0.0680		K/W
Temperature under switching conditions	$T_{vj, op}$		-40		150	°C

4 Diode, Rectifier

Table 7 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Repetitive peak reverse voltage	V_{RRM}		$T_{vj} = 25 \text{ °C}$	1800	V
Maximum RMS forward current per chip	I_{FRMSM}	$T_C = 95 \text{ °C}$		150	A
Maximum RMS current at rectifier output	I_{RMSM}	$T_C = 95 \text{ °C}$		150	A
Surge forward current	I_{FSM}	$t_p = 10 \text{ ms}$	$T_{vj} = 25 \text{ °C}$	1460	A
			$T_{vj} = 150 \text{ °C}$	1260	
I^2t - value	I^2t	$t_p = 10 \text{ ms}$	$T_{vj} = 25 \text{ °C}$	10700	A²s
			$T_{vj} = 150 \text{ °C}$	7940	

Table 8 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$T_{vj} = 150 \text{ °C}$, $I_F = 150 \text{ A}$		1.00		V
Threshold voltage	$V_{(TO)}$	$T_{vj} = 150 \text{ °C}$		0.76		V
Slope resistance	r_t	$T_{vj} = 150 \text{ °C}$		1.6		mΩ
Reverse current	I_r	$T_{vj} = 150 \text{ °C}$, $V_R = 1800 \text{ V}$		1		mA
Thermal resistance, junction to case	R_{thJC}	per diode			0.364	K/W
Thermal resistance, case to heatsink	R_{thCH}	per diode, $\lambda_{Paste} = 1 \text{ W/(m}^2\text{K)}$ / $\lambda_{grease} = 1 \text{ W/(m}^2\text{K)}$		0.0680		K/W
Temperature under switching conditions	$T_{vj, op}$		-40		150	°C

Note: The current under continuous operation is limited to 50 A rms per connector pin.

5 NTC-Thermistor

Table 9 Characteristic values


Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Rated resistance	R_{25}	$T_{NTC} = 25\text{ °C}$		5		kΩ
Deviation of R_{100}	$\Delta R/R$	$T_{NTC} = 100\text{ °C}, R_{100} = 493\text{ Ω}$	-5		5	%
Power dissipation	P_{25}	$T_{NTC} = 25\text{ °C}$			20	mW
B-value	$B_{25/50}$	$R_2 = R_{25} \exp[B_{25/50}(1/T_2 - 1/(298,15\text{ K}))]$		3375		K
B-value	$B_{25/80}$	$R_2 = R_{25} \exp[B_{25/80}(1/T_2 - 1/(298,15\text{ K}))]$		3411		K
B-value	$B_{25/100}$	$R_2 = R_{25} \exp[B_{25/100}(1/T_2 - 1/(298,15\text{ K}))]$		3433		K

Note: Specification according to the valid application note.

6 Characteristics diagrams


output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$
 $V_{GE} = 15\text{ V}$




output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$
 $T_{vj} = 150\text{ °C}$




transfer characteristic (typical), IGBT, Inverter

$I_C = f(V_{GE})$
 $V_{CE} = 20\text{ V}$



switching losses (typical), IGBT, Inverter


$E = f(I_C)$
 $R_{Goff} = 0.91\text{ }\Omega$, $R_{Gon} = 0.91\text{ }\Omega$, $V_{CE} = 900\text{ V}$, $V_{GE} = -15 / 15\text{ V}$



6 Characteristics diagrams


switching losses (typical), IGBT, Inverter

$E = f(R_G)$
 $I_C = 150\text{ A}$, $V_{CE} = 900\text{ V}$, $V_{GE} = -15 / 15\text{ V}$




switching times (typical), IGBT, Inverter

$t = f(I_C)$
 $R_{Goff} = 0.91\text{ }\Omega$, $R_{Gon} = 0.91\text{ }\Omega$, $V_{CE} = 900\text{ V}$, $V_{GE} = -15 / 15\text{ V}$,
 $T_{vj} = 150\text{ }^\circ\text{C}$




switching times (typical), IGBT, Inverter

$t = f(R_G)$
 $I_C = 150\text{ A}$, $V_{CE} = 900\text{ V}$, $V_{GE} = -15 / 15\text{ V}$, $T_{vj} = 150\text{ }^\circ\text{C}$



transient thermal impedance , IGBT, Inverter


$Z_{th} = f(t)$



6 Characteristics diagrams


reverse bias safe operating area (RBSOA), IGBT, Inverter

$I_C = f(V_{CE})$
 $R_{Goff} = 0.91 \Omega$, $V_{GE} = \pm 15 \text{ V}$, $T_{vj} = 150 \text{ }^\circ\text{C}$




forward characteristic (typical), Diode, Inverter

$I_F = f(V_F)$




switching losses (typical), Diode, Inverter

$E_{rec} = f(I_F)$
 $V_{CE} = 900 \text{ V}$, $R_{Gon} = R_{Gon}(\text{IGBT})$



switching losses (typical), Diode, Inverter


$E_{rec} = f(R_G)$
 $V_{CE} = 900 \text{ V}$, $I_F = 150 \text{ A}$



6 Characteristics diagrams


transient thermal impedance , Diode, Inverter

$Z_{th} = f(t)$




Forward characteristic (typical), Diode, Rectifier

$I_F = f(V_F)$




Transient thermal impedance, Diode, Rectifier

$Z_{th} = f(t)$



Temperature characteristic (typical), NTC-Thermistor

$R = f(T_{NTC})$






Figure 2

8 Package outlines




Figure 3

Revision history

Revision history

Document revision	Date of release	Description of changes
1.00	2021-05-11	Final datasheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2021-05-11

Published by

Infineon Technologies AG
81726 Munich, Germany

© 2021 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-AAZ508-001

IMPORTANT NOTICE

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

WARNINGS

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Infineon:](#)

[F4150R17N3P4B58BPSA1](#)