

EMERALD-MAXI-A

Asymmetric beam

TECHNICAL SPECIFICATIONS:

Dimensions 33.0 x 25.0 mm

Height 11 mm Fastening glue, pin **ROHS** compliant yes 1

MATERIAL SPECIFICATIONS:

Component **Type EMERALD-MAXI-A** Single lens



Material Colour **Finish PMMA** clear

ORDERING INFORMATION:

» Box size: 480 x 280 x 300 mm


Component Qty in box MOQ MPQ Box weight (kg)

1330 280 C14522 EMERALD-MAXI-A 70 7.7



PRODUCT DATASHEET

C14522_EMERALD-MAXI-A





PHOTOMETRIC DATA (MEASURED):


CREE \$

LED XHP50.2 FWHM Asymmetric

Efficiency 92 %

Peak intensity 1.2 cd/lm LEDs/each optic 1

Light colour White Required components:



CREE 🕏


LED XM-L

FWHM Asymmetric

Efficiency 94 %
Peak intensity 2 cd/lm

LEDs/each optic 1

Light colour White Required components:



CREE \$

LED XM-L2


FWHM Asymmetric

Efficiency 92 %

Peak intensity 1.9 cd/lm

LEDs/each optic 1 Light colour White

Required components:




DESCRIPTION LUMILEDS

LED LUXEON M/MX FWHM Asymmetric

Efficiency 92 %
Peak intensity 1.2 cd/lm

LEDs/each optic 1
Light colour White
Required components:



Published: 13/09/2019




PHOTOMETRIC DATA (MEASURED):



LED LUXEON MZ **FWHM** Asymmetric

Efficiency 93 % Peak intensity 2.1 cd/lm


LEDs/each optic 1 Light colour White Required components:



LED LH181B **FWHM** Asymmetric

Efficiency 94 % Peak intensity 4 cd/lm LEDs/each optic 1

Light colour White Required components:



Published: 13/09/2019




PHOTOMETRIC DATA (SIMULATED):

CREE \$

LED J Series 5050 **FWHM** Asymmetric Efficiency 90 % Peak intensity 1.4 cd/lm LEDs/each optic White

Light colour Required components:



CREE ÷


LED XHP50 **FWHM** 20.8 + 79.1° 92 % Efficiency Peak intensity 1 cd/lm

LEDs/each optic 1 Light colour White Required components:

CREE ÷

LED XP-G3 **FWHM** Asymmetric Efficiency 93 %


Peak intensity 1.4 cd/lm LEDs/each optic Light colour White Required components:



OSRAM Opto Semiconductors

LED OSCONIQ P 7070 **FWHM** Asymmetric Efficiency 87 % Peak intensity 1.2 cd/lm LEDs/each optic

White Light colour Required components:



Published: 13/09/2019



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Ledil:

C14522_EMERALD-MAXI-A