PART NUMBER	SSL-LX3044LID-TR	REV.	Α
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
10.13.11	E.C.N. #10BRDR.		Α

ø3.20 [ø0.126]	\$2.90 [\$0.114]		
1.00 [0.039] — FRONT SURFACE — HOUSE —	12.7 [0.500] + + + + + + + + + + + + + + + + + +	4.60 [0.181] + - 0.50 [0.020] SGR. - 2.54 [0.100]	0.70 [0.028]
	→	2.54 [0.100]	U.7U [U.U20] → I I→

ELECTRO-OPTICAL CH	IARACTERIS	STICS TA=25°	С	I _f =20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		2.0	2.5	Vf	
REVERSE VOLTAGE	5.0			٧r	I _r =100μΑ
AXIAL INTENSITY		30		mcd	$I_f = 20 \text{mA}$
	1.0			mcd	$I_f = 2mA$
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	RED				
FPOXY LENS FINISH:	RED DIE	FUSED			

2TIMI I	ΛF	SVEE	OPERATION	ΔТ	25°€	
LIMII 2	UΓ	SALE	UPERAIIUN	ΑI	Z3 U	

PARAMETER	MAX	UNITS				
PEAK FORWARD CURRENT*	150	mA				
STEADY CURRENT	30	mA				
POWER DISSIPATION	105	mW				
DERATE FROM 25°C	- 1.6	mW/°C				
OPERATING, STORAGE TEMP.	- 40 TO +85	•C				
SOLDERING TEMP.	+ 260	°C				
2.0mm FROM BODY		3 SEC. MAX				

* t<10µS

TAPE FEED DIRECTION ----

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= $^{+0.00}_{-0.00}$ PRECISION MAX.= $^{+0.00}_{-0.00}$ PRECISION $^{+0.00}_{-0.00}$ MAX.= $^{+0.00}_{-0.00}$ PRECISION $^{-0.00}_{-0.00}$ PRECISION $^{-0.00}_{-0$ UNCONTROLLED DOCUMENT DATE: 10.13.11 DRAWN BY: AΒ T-3mm (T-1) 635nm RED LED, RED DIFFUSED, LOW CURRENT OPERATION, TAPE & REEL.

Creating LED and LCD Solutions Together™ WEB: WWW.LUMEX.COM

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

PAGE: 1 OF 1 CHKD BY: SS SCALE: NTS APRVD BY: SS (Pb) UNIT: mm [INCH]

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSL-LX3044LID-TR