


Broadband Eight -Way Power Divider, 20 - 2000 MHz

Rev. V2

Features

- Two-Decade Frequency Range
- High Isolation 20 dB Min
- Typical Midband VSWR 1.2:1

C-18



Guaranteed Specifications: From -55°C to +85°C


Frequency Range		20-2000 MHz
Insertion Loss (less coupling)	20-600 MHz 600-1000 MHz 1000-2000 MHz	1.0 dB Max 1.4 dB Max 3.0 dB Max
Isolation		20 dB Min
Amplitude Balance	20-600 MHz 600-1000 MHz 1000-2000 MHz	0.6 dB Max 0.6 dB Max 1.2 dB Max
Phase Balance	20-600 MHz 600-1000 MHz 1000-2000 MHz	5° Max 5° Max 15° Max
VSWR (All Ports)	20-60 MHz 60-600 MHz 600-1000 MHz 1000-2000 MHz	1.7:1 Max 1.4:1 Max 2.0:1 Max 2.0:1 Max





Broadband Eight -Way Power Divider, 20 - 2000 MHz

Rev. V2

Typical Performance Curves







Ordering Information

Part Number	Package
DS-808-4 BNC	Connectorized
DS-808-4 SMA	Connectorized
DS-808-4 TNC	Connectorized
DS-808-4 N	Connectorized

Operating Characteristics

Parameter	Absolute Maximum	
Impedance	50 Ohms Nominal	
Maximum Power Rating or Input Power	5.0 Watt Max	
Internal Load Dissipation	0.5 Watt Max	
Enviornmental MIL-STD-202 screening available.		

^{*} All specifications apply with 50 ohm source and load impedance. This product contains elements protected by United States Patent Number 3,325,587.

DS-808-4



Broadband Eight -Way Power Divider, 20 - 2000 MHz

Rev. V2

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

MACOM:

DS-808-4SMA DS-808-4TNC DS-808-4BNC DS-808-4N