THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. **WEIGHT PANDUIT** NOMINAL В С STATIC CABLE O.D. LOAD** PART in. in. lbs./(a) in. (mm) lbs./(g) 100 pcs. NUMBER* in./(mm) (mm) (mm) 0.120 0.77 0.12 0.23 0.14 0.21 A1C12-A (3.0)(19.6)(3.0)(5.8)(64) (95) 0.250 0.25 0.32 0.91 0.38 0.14 A1C25-A A1C25-A (6.4)(23.1)(6.4)(9.7)(64) (145)ACTUAL SIZE 0.375 1.04 0.38 0.51 0.14 0.42 A1C38-A (9.7)(190)(9.5)(26.4)(64) (13.0)REF 0.50 0.500 1.17 .50 0.64 0.14 A1C50-A (12.7)(64) (227) (29.7)(12.7)(16.3)NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE BY PANDUIT WITH RESPECT TO ADHESIVE BOND PERFORMANCE. AMONG OTHER THINGS, THE CONDITIONS UNDER WHICH THESE 0.59 MOUNTS MAY BÉ APPLIED AND/OR THE SURFACE TO WHICH (15.0)THEY MAY BE APPLIED ARE BEYOND PANDUIT'S CONTROL. TO APPLY MOUNT 1) REMOVE PROTECTIVE LINER. B REF 2) PLACE IN DESIRED LOCATION. 3) APPLY PRESSURE TO MOUNT. NOTES: *1. SEE CURRENT PRICE SHEET FOR PART NUMBER — TEAR TAB SUFFIX DESIGNATION FOR PACKAGE SIZE. -0.63-(16.0)ADHESIVE TAPE--PRESSURE SENSITIVE FOAM .040 (1.02) THICK WITH RUBBER ADHESIVE AND PROTECTIVE LINER. **MOUNT IS DESIGNED TO SUPPORT LISTED MAXIMUM STATIC (DIMENSIONS IN PARENTHESES ARE IN METRIC.) LOAD ON A CLEAN, DRY, SMOOTH, GREASE-FREE SURFACE. CAD FILENAME/LAYERS GB0431BA_PB_A1CCLIPS_02 TINLEY PARK, ILLINOIS A1C-A ADHESIVE CLIP UNLESS OTHERWISE SPECIFIED, UNLESS OTHERWISE SPECIFIED. DIMENSIONAL TOLERANCES ARE: ALL DIMENSIONS ARE GIVEN (.X) ±0.1(2.5) (.XXX) ± 0.020(.5) (.XX) ±0.05(1.3) ANGLES ± 5° ADDED REF TO DIM 2 6/15/01 LGG GB0431BA 2 IN INCHES, THIRD ANGLE PROJECTION. DRAWN BY SCALE MAT'L: NONE 2-16-94 SJSU REVERSE TEAR TAB GB0431BA 1 SJSU GRAY DATE DRAWING NO. DWG l11-5-93 | SJSU INITIAL RELEASE GB0431BA R 11-5-93 PVC Α GB0431BA CHK 'D DATE DESCRIPTION SUP RFV BY CHK ECN - R CUST SIZE

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

A1C12-A-C8 A1C25-A-C8 A1C38-A-C8 A1C50-A-C8