XVS72BMWP



Main

Range of product	Harmony XVS
Product or component type	Electronic alarm
Device short name	XVS

Complementary

Color	White	
Material	ABS (acrylonitrile butadiene-styrene) (body) PC (polycarbonate) (terminal cover)	
Product weight	0.4 lb(US) (0.18 kg)	
Marking	CE	
Overvoltage category	Class II conforming to EN/IEC 61140	
Mounting support	72 mm DIN rail	_
[Us] rated supply voltage	1224 V DC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	117 mAat 12 V 125 mAat 24 V 158 mAat 12 V 200 mAat 24 V	
Clamping connection capacity	<= 1 x 1.5 mm²	
Width	2.83 in (72 mm)	
Height	2.83 in (72 mm)	
Depth	2.73 in (69.3 mm)	

Environment

discrete output type	PNP	
signalling type	16 tones alarm	
standards	EN/IEC 61000-6-2 EN/IEC 61000-6-3 UL 464	
product certifications	UR	
protective treatment	TC	
ambient air temperature for storage	-31158 °F (-3570 °C)	
ambient air temperature for operation	14122 °F (-1050 °C)	
IP degree of protection	IP54 (panel mounted) conforming to EN/IEC 60529	
noise level	090 dB (continuous or intermittent tone)at 1 m	

Offer Sustainability

Not Green Premium product
Compliant - since 1346 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold
WARNING: This product can expose you to chemicals including:

of California to cause cancer and birth defects or other and birth defects or other reproductive harm.

Lead and lead compounds, which is known to the State Lead and lead compounds, which is known to the State of California to cause cancer


For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

Electronic Alarm

Dimensions





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XVS72BMWP