

STANDARD VERSION

SCALA NON IMPERIATIVA
(DO NOT SCALE)
DIMENSIONI IN
DIMENSIONS IN mm

METRIC

PROTEZIONE EUROPEA
(EUROPEAN PROTECTION)

G.TY REQ'D PER ASS'Y				PART. LIST		
				PART. NO.	DESCRIPTION	QTY
				282267-1	SEC. LOCK 19 POS.	4
				282266-1	SEC. LOCK 18 POS.	3
				282268-1	COVER	2
				282264-2	HOUSING ASS'Y	1

SECTION A-A

PER RIFERIM.
FOR REF. ONLY

PRE ASSEMBL.
PRE-ASS'Y

BLACK

1

282195-2

COLOUR

MATERIALE
(MATERIAL)

NUMERO
(PART NUMBER)

CUSTOMER DWG.
FOR REFERENCE ONLY

DISEGNO PER CLIENTE
SOLO PER RIFERIMENTO

THIS DRAWING IS UNPUBLISHED
COPYRIGHT IS BY AMP INCORPORATED, HARTFORD, PA. ALL INTERNATIONAL RIGHT
RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENT AND/OR PATENT PENDING
TOLLERANZE, SE NON
DIVERSAMENTE SPECIFICATO
TOLERANCES, UNLESS
OTHERWISE SPECIFIED

DIAM. ISOLANTE
INS. DIA. RANNO
1.7-2.1 mm
2.4-3.0 mm

RANGO FILO
WIRE RANNO
0.5-1.0 mm²
1.5-2.5 mm²

SCALA
(SCALE)

AMP ITALIA S.p.A.
Corso P.LLI Garvi, 18
COLLENO (TORINO)

DIS. E.CINI
(GR.) 11 MAY 1980

DESCRIZIONE
DESCRIPTION
35 P. SPLASH PROOF CONN.
WITH SECONDARY LOCK

RELEASED FOR PRODUCTION
EC ET00-0175-83

CON. COLORE
COLOUR
TARTARI

LOC. SIZE
LOC. SIZE
I A3 C-282195

REV. 1
FOR 10
DI 2

CAVITA' PER SFIATO "B"
(VEDI TERMINALE PN 282270-12)
VENT-HOLE

VISTA CONN.
SENZA COPERCHIO
VIEW HSG
WITHOUT COVER

CAVITA' OSTRUITA "A"
CLOSED HOLE

N°35 CAVITA' ADATTE PER TERMINALE
"AMP JUNIOR POWER TIMER" E RELATIVI GOMMINI.
N°35 CAVITIES SUITABLE
FOR "AMP JUNIOR POWER TIMER" CTS.

NOTES:

- 1 MATERIALS, HSG, COVER AND SEC. LOCKS IN PA 66 GLASS FILLED
-SEALING OF SILICONE RUBBER
- 2) ITEMS ①, ②, ③, ④ PACKAGE INTO A CARTON BOX.

NOTE:

- 1 MATERIALI: -BLOCCHETTO, COPERCHIO E SEC. LOCK IN PA 66 CAR. VETRO
-GUARNIZIONE IN SILICONE (COL. ROSSO)
- 2) I PART. ①, ②, ③, ④ SONO CONFEZIONATI IN KIT
IN UN'UNICA SCATOLA DI CARTONE.

SCALA NON IMPERATIVA
(DO NOT SCALE)

DIMENSIONI IN mm
DIMENSIONS IN mm



**PROTEZIONE EUROPEA
EUROPEAN PROTECTION**

A grid with a diagonal label "SEE SHEET 1 of 2".

(FINISH / COLOUR)		(MATERIALE / MATERIAL)		(NUMERO / PART NUMBER)	
CUSTOMER DWG. FOR REFERENCE ONLY			DISEGNO PER CLIENTE SOLO PER RIFERIMENTO		
THIS DRAWING IS UNPUBLISHED					
© COPYRIGHT 1985 BY AMP INCORPORATED, HARTFORD, CT. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN PATENT AND/OR PATENT PENDING. TOLLERANZA, SE NON DIVERSAMENTE SPECIFICATO (TOLERANCES, UNLESS OTHERWISE SPECIFIED)					
± 0.3 ANGOLI (CAMELS) ± 2°		DIAH. ISOLANTE (INS. DIA. RANDED) -		RANGO FILO (WIRE RANDED) -	
		AMP		AMP ITALIA S.p.A. Corso P.L.I. Garvi, 18 COLLENO (TORINO)	
DIS. E.CINI (DR.) 30 NOV. '92		DESCRIZIONE (DESCRIPTION) 35 P. SPLASH PROOF CONN. with SECONDARY LOCK			
CONT. - 23 NOV. '93 (CNS) C. TARTARI		LOC. SIZE NUMERO (CNS) (CNS) (CNS)		REV. FOR LIO (CNS) (CNS)	
APP. CAPP. -		I A3 C-282195		A 2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[282195-2](#)