




Bestückungsplan / Contact layout



■ = bestückt / assembled

Lochbild für Leiterplatte
(Bestückungsseite)

Board hole pattern
(Component mounting side)



- 1) $\phi 0.6 \pm 0.05$ Durchmesser des metallisierten Loches
 $\phi 0.6 \pm 0.05$ Diameter of finished plated-through hole
 $\phi 0.7 \pm 0.02$ Bohrungsdurchmesser des Loches
 $\phi 0.7 \pm 0.02$ Diameter of drilled hole

Schichtaufbau im metallisierten Loch siehe Zeichnung 114406
 Metal plating of plating-through hole see drawing 114406

Fehlende Maße und Angaben nach IEC 61076-4-101
 Missing information and dimensions per 61076-4-101

Copyright by ERNI Production GmbH & Co. KG
 Proprietary notice pursuant to ISO 16018 to be observed.

Information: Distanzstück H=9,6 / distance h=9,6		Tolerances  All Dimensions in mm		Scale 2:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation ERmet-FS Federleiste B <i>ERmet-Female Straight Type B</i>
b Index		05.12.2014 Date		114021 I A3
		ERNI www.ERNI.com		Class ERMB

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[114021](#)